

How to Operate the Toilet



All Hunter yachts have now been fitted with Jabsco toilets. Please ensure all your crew know how to operate the toilet correctly. DO NOT PUT INAPPROPRIATE MATERIAL IN THE BOWL - (the lads at the Yard do not enjoy unblocking toilets!)

- ▼ The toilets have a Twist 'n' Lock action safety handle which guards against flooding and waste backflow by locking the waste outlet valve shut. Always ensure the handle is locked when not in use.
- ▼ Before use, ensure that there is enough water in the bowl to prevent the toilet paper becoming compacted at the bottom of the bowl.

If the bowl is empty, move the flush control lever to the OPEN (←) position and pump the handle up and down until the flushing pump is primed and water enters the bowl.

Then SHUT (→) the Flush Control.

- ▼ Operate the pump with long, smooth strokes for efficient and easy operation.
- ▼ during use, pump as necessary to keep the contents of the bowl low enough for comfort.
- ▼ Use good quality soft household toilet paper, but do not use more than is necessary.
- ▼ after use, keep the Flush Control SHUT (→) and pump until the bowl is empty.
- ▼ When the bowl is empty OPEN (←) the Flush Control again, and continue to pump until all the waste has left the boat - at least 7 complete up/down strokes.

Then SHUT (→) the Flush Control and pump until the bowl is empty. Always leave the bowl empty to minimise odour and spillage.

Leave the Flush Control in the SHUT (→) position.

Push the pump handle down and twist to lock.